

**BEST AVAILABLE COPY**FUJO 20.466  
10/609,492In the Claims:

Please amend the claims as follows:

1. (currently amended) An error rate control apparatus for use in a communications system which maps a data signal and a control signal to a physical channel, said control signal used to receive said data signal, said apparatus comprising:
  - a control signal error rate computation unit computing an error rate of the control signal;
  - and
  - a power variable unit transmitting the control signal after changing transmission power of the control signal based on a value of the error rate.
2. (previously presented) The apparatus according to claim 1, wherein  
said communications system is a W-CDMA system.
3. (previously presented) The apparatus according to claim 1, wherein  
said control signal is a TFCI, a PILOT, or a TPC in a signal format of a W-CDMA system.
4. (cancelled).
5. (currently amended) The apparatus according to ~~claim 4~~ claim 1, wherein:
  - said data signal is a transport channel signal of a W-CDMA system; and
  - when a plurality of transport channels are included in a physical frame, the error rate of the control signal is computed based on a number of the transport channels in the physical frame.

FUJO 20.466  
10/609,492

6. (currently amended) The apparatus according to ~~claim 4~~ claim 1, wherein:

said data signal is a transport channel signal of a W-CDMA system; and  
when the transport channel is transmitted covering a plurality of physical frames, and  
when a value of the control signal of each physical frame is inconsistent among the plurality of  
physical frames, an error rate is computed with the control signal considered to be erroneous.

7. (currently amended) The apparatus according to ~~claim 4~~ claim 1, wherein:

said data signal is a transport channel signal of a W-CDMA system; and  
when the transport channel comprises a plurality of transport blocks, and the plurality of  
transport channels are all erroneous, an error rate of the control signal is computed with the  
control signal considered to be erroneous.

8. (currently amended) An error rate control method for use with a communications system

which maps a data signal and a control signal to a physical channel, said control signal used to  
receive said data signal, said method comprising:

computing an error rate of the control signal; and

transmitting the control signal after changing transmission power of the control signal  
based on a value of the error rate.

9. (previously presented) The method according to claim 8, wherein said communications  
system is a W-CDMA system.

10. (previously presented) The method according to claim 8, wherein said control signal is a  
TFCI, a PILOT, or a TPC in a signal format of a W-CDMA system.

FUJO 20,466  
10/609,492

11. (cancelled)

12. (currently amended) The method according to ~~claim 11~~ claim 8, wherein:

said data signal is a transport channel signal of a W-CDMA system; and

when a plurality of transport channels are included in a physical frame, the error rate of the control signal is computed based on a number of the transport channels in the physical frame.

13. (currently amended) The method according to ~~claim 11~~ claim 8, wherein:

said data signal is a transport channel signal of a W-CDMA system; and

when the transport channel is transmitted covering a plurality of physical frames, and when a value of the control signal of each physical frame is inconsistent among the plurality of physical frames, an error rate is computed with the control signal considered to be erroneous.

14. (currently amended) The method according to ~~claim 11~~ claim 8, wherein:

said data signal is a transport channel signal of a W-CDMA system; and

when the transport channel comprises a plurality of transport blocks, and the plurality of transport channels are all erroneous, an error rate of the control signal is computed with the control signal considered to be erroneous.

15. (currently amended) A radio communication apparatus transmitting a data signal and a

control signal to another radio communication apparatus, said control signal used to receive said data signal, said apparatus comprising:

FUJO 20.466  
10/609,492

a control unit for controlling transmission power of said control signal separately from transmission power of said data signal based on an error condition of said control signal received by said other communication apparatus.

16. (currently amended) A radio communication apparatus transmitting a data signal and a control signal to another radio communication apparatus, said control signal used to receive said data signal, said apparatus comprising:

a control unit for controlling transmission power of said control signal separately from transmission power of said data signal based on a feedback signal from the other radio communication apparatus.

17. (original) The radio communication apparatus of claim 16, wherein said data signal is a transport channel signal of a W-CDMA system, said control signal indicates a format of the transport channel and said apparatus maps the transport channel and said control signal to a physical channel.

18. (currently amended) A radio communication apparatus which is capable of transmitting a data signal and a control signal to another radio communication apparatus, wherein transmission power of said control signal is deviated from said transmission power of said data signal by a certain value, said control signal used to receive said data signal, said apparatus comprising:

a control unit for controlling transmission power of said control signal to change said certain value based on an error condition of said control signal received by said other radio communication apparatus.

FUJO 20,466  
10/609,492

19. (currently amended) A radio communication apparatus which is capable of transmitting a data signal and a control signal to another radio communication apparatus, wherein transmission power of said control signal is deviated from said transmission power of said data signal by a certain value, said control signal used to receive said data signal, said apparatus comprising;

a control unit for controlling transmission power of said control signal to change said certain value based on a feedback signal from said other radio communication apparatus.

20. (currently amended) A method for controlling transmission power of a control signal for a channel shared by plural users, comprising:

determining transmission power of a channel dedicated to a user;

setting transmission power of a timeslot of said control signal in relation to said transmission power of the channel dedicated to a user that uses the timeslot transmitting signals over said control channel with the set power, said control signal used to receive said data signal.

21. (original) A method for controlling a transmission power of a control channel comprising:

determining transmission power of a downlink dedicated physical channel based on the received TPC command; and

determining transmission power of a shared control channel transmitted to each mobile station by using a power offset value related to transmission power of the downlink dedicated physical channel, wherein said power offset value is based on a feedback signal from said mobile stations.

22. (currently amended) A control information transmitting method of a mobile communication system, said control information transmitted by a control signal, said control signal mapped with

FUJO 20.466  
10/609,492

a data signal to a physical channel, said physical channel transmitted by a radio communication apparatus, said control signal used to receive said data signal, said method comprising:

determining a power offset value of the control signal for the physical channel based on a feedback signal from another radio communication apparatus;

controlling transmission power of said control signal separately from transmission power of said data signal by using the transmitted PO value.

23. (currently amended) A method for controlling transmission power of a control channel in a high-speed-data packet access service of a mobile communications system in which a user equipment receives a data signal through a high speed-downlink shared channel on the basis of control information transmitted through the control channel, said control signal used to receive said data signal, the method comprising:

determining a transmission power of the control channel based on a response from the user equipment;

controlling transmission power of said control channel separately from transmission power of said data signal based on the determining step.

24. (original) The method according to claim 23, wherein said mobile communications system is a W-CDMA system and the control channel is a TFCI, a PILOT, or a TPC in a signal format of the W-CDMA system.

25. (original) The method according to claim 23, wherein the data signal is a transport channel signal of a W-CDMA system, said control channel indicates a format of the transport channel

FUJO 20.466  
10/609,492

and the method maps one or more transport channels and the control channel to a physical channel.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**